

ABOVE GROUND TANK VALVES

ANTI-SYPHON VALVE

Application -

Reducing fire hazards and preventing fuel spillage should a line rupture. The flow would automatically stop the syphon effect.

*Also available with pressure relief for thermal expansion (403PR).

Part Number - 403



UNIVERSAL
Advantage

Only from Universal! – No need to specify head settings! Everything is included to cover an operating range of 0' to 20'.

Features -

- ✓ Precision machined valve seats
- ✓ Automatic shut off syphon effect
- ✓ Prevents fuel spillage
- ✓ No need to specify head settings when ordering

Construction -

- Zinc plated cast iron body
- Buna-N seals

Model	Thread Size	Weight (lbs.)	A	B
403-34	3/4"	5.0	4-3/4"	2-3/8"
403PR-34	3/4"	5.0	4-3/4"	2-3/8"
403-10	1"	4.8	4-3/4"	2-3/8"
403PR-10	1"	4.8	4-3/4"	2-3/8"
403-15	1-1/2"	4.6	4-3/4"	2-3/8"
403PR-15	1-1/2"	4.6	4-3/4"	2-3/8"
403-20	2"	7.2	5-3/8"	2-1/2"
403PR-20	2"	7.2	5-3/8"	2-1/2"

