



NO.	DESCRIPTION	MFG.	QUAN.
1	PUMP MODEL# 10GC61312 (CW) 10GC61412 (CCW)	ALBANY	1
2	HP V-PH-HZ RPM TEFC MOTOR	LEESON	2
3	DUPLEX BASKET STRAINER 1" NPT C/W 60 MESH S.S. SCREEN	ALBANY	1
4	BALL VALVE 1" NPT	NIBCO	4
5	CHECK VALVE 1" NPT	UNITED	2
6	RELIEF VALVE 3/4" NPT	FULFLO	2
7	ALL 1" NPT PIPING EXCEPT RELIEF VALVE (3/4")	-	-
8	PRESSURE GAUGE 100 MM. DIA. (4")	WINTERS	2
9	COMPOUND GAUGE 30"-0-30 PSI 100 MM. DIA. (4")	WINTERS	2
10	15" CHANNEL BASE WITH 1.5" DRIP LIP (WITH DRAIN) UNDER PUMPS AND STRAINER	ALBANY	1
11	IN-LINE CHECK VALVE	NIBCO	2
12	HIGH/LOW PRESSURE SHUT-OFF SWITCH	ASCO	1
13	BALL VALVE 1" NPT	M.A. STEWART	1

UNIT ADHERES TO CSA STD. B139
 CONDITIONS :
 LIQUID DIESEL FUEL OIL
 CAPACITY 10 USGPM (MAX.)
 PRESSURE 150 PSI (MAX.)
 VISCOSITY 50 SSU
 SUCTION 17" HG. MAX

ALBANY PUMP CO. LTD.	
DRWN. SMB	420 HARRY WALKER PARKWAY NEW MARKET, ONT. CANADA L3Y 8P5
DATE 5/10/07	
SCALE NONE	DUPLEX FUEL OIL UNIT
CHK'D	10 GALLON DUPLEX

MODEL # FODUP/10G/BS

This drawing and the information depicted therein is the property of Albany Pump Co. Ltd. Copies are issued in strict confidence and shall not be reproduced, copied or used as the basis for the manufacture or sale of products without prior written permission of Albany Pump Co.