



NO.	DESCRIPTION	MFG	QUAN.
1	PUMP MODEL# 05GC61412	ALBANY	1
2	1/2 HP, 1725 RPM TEFC 56C MOTOR	—	1
3	SBS-100 BASKET STRAINER C/W 60 MESH S.S. SCREEN	ALBANY	1
4	BALL VALVE 3/4"NPT		2
5	CHECK VALVE 3/4"NPT		1
6	RELIEF VALVE 1/2"NPT	FULFLO	1
7	ALL 3/4"NPT PIPING EXCEPT RELIEF VALVE (1/2")	—	—
8	PRESSURE GAUGE 100 MM DIA.	WINTERS	1
9	COMPOUND GAUGE 100 MM DIA. 30"-0-30 PSI	WINTERS	1
10	15" CHANNEL BASE WITH 2" DRIP LIP (WITH DRAIN) UNDER PUMP AND STRAINER	ALBANY	1
11	HIGH / LOW PRESSURE SHUT OFF SWITCH WITH SNUBBER	ASCO	1

UNIT ADHERES TO CSA STD. B139

LIQUID DIESEL FUEL OIL  
 CAPACITY 5 USGPM MAX.  
 PRESSURE 150 PSI MAX.  
 VISCOSITY 50 SSU  
 SUCTION 20 FT. MAX.

SEE SEPARATE DRAWING FOR CONTROL PANEL

**ALBANY PUMP CO. LTD.**

DRWN. SMB 420 HARRY WALKER PARKWAY  
 NEW MARKET, ONT. CANADA L3Y 8P5

DATE 4/30/2007  
 SCALE NONE

CHK'D FOSIM/05GC/BS

MODEL# FOSIM/05GC/BS

SIMPLEX FUEL OIL UNIT