



NO.	DESCRIPTION	MFG	QUAN.
1	PUMP MODEL# 10GC61412	ALBANY	1
2	1/2 HP, 1725 RPM TEFC 56C MOTOR	—	1
3	SBS-100 BASKET STRAINER C/W 60 MESH S.S. SCREEN	ALBANY	1
4	BALL VALVE 1" NPT		2
5	CHECK VALVE 1" NPT		1
6	RELIEF VALVE 3/4" NPT	FULFLO	1
7	ALL 1" NPT PIPING EXCEPT RELIEF VALVE (3/4")	—	—
8	PRESSURE GAUGE 100 MM DIA.	WINTERS	1
9	COMPOUND GAUGE 100 MM DIA. 30"-0-30 PSI	WINTERS	1
10	15" CHANNEL BASE WITH 2" DRIP LIP (WITH DRAIN) UNDER PUMP AND STRAINER	ALBANY	1
11	HIGH / LOW PRESSURE SHUT OFF SWITCH WITH SNUBBER	ASCO	1

UNIT ADHERES TO CSA STD. B139

LIQUID DIESEL FUEL OIL  
 CAPACITY 10 USGPM MAX.  
 PRESSURE 150 PSI MAX.  
 VISCOSITY 50 SSU  
 SUCTION 20 FT. MAX.

SEE SEPARATE DRAWING FOR CONTROL PANEL

**ALBANY PUMP CO. LTD.**

DRWN. SMB 420 HARRY WALKER PARKWAY  
 NEW MARKET, ONT. CANADA L3Y 8P5

DATE 4/30/2007

SCALE NONE

CHK'D FOSIM/10GC/BS

MODEL# FOSIM/10GC/BS